

## BI-METAL HIGH SPEED STEEL – Power Hacksaw Blades

The bi-metal construction of these power hacksaw blades provides exceptional cutting action in a wide variety of applications. The high speed steel teeth and durable alloy steel backing resist breakage and can handle irregular shaped work pieces and interrupted cuts.

### BI-METAL HIGH SPEED STEEL Power Hacksaw Blades



	Dimensions Length x Width x Thickness	Pinhole Diameter Inch (mm)	TPI (25mm)	Catalog No.	EDP No.
<b>12"</b>	12" x 1-1/8" x .050" 300mm x 28.6mm x 1.25mm	.281" (7.00mm)	10	BS1210-5	40097
			14	BS1214-5	40098
<b>14"</b>	14" x 1-1/8" x .050" 350mm x 28.6mm x 1.25mm	.281" (7.00mm)	10	BS1410-5	40099
			14	BS1414-5	40100
	14" x 1-3/8" x .062" 350mm x 35mm x 1.66mm	.281" (7.00mm)	6	BS1406-6	40101
			10	BS1410-6	40102
	14" x 1-5/8" x .075" 350mm x 41mm x 2mm	.281" (7.00mm)	6	BS1406-7	40105
<b>17"</b>	17" x 1-3/8" x .062" 425mm x 35mm x 1.6mm	.281" (7.00mm)	6	BS1706-6	40264
			10	BS1710-6	40265
<b>18"</b>	18" x 1-3/8" x .062mm 450mm x 35mm x 1.6mm	.281" (7.00mm)	6	BS1806-6	40267
			10	BS1810-6	40268
	18" x 1-5/8" x .075" 450mm x 41mm x 2mm	.281" (7.00mm)	4	BS1804-7	40272
			6	BS1806-7	40273
	18" x 1-7/8" x .088" 450mm x 48mm x 2.25mm		4	BS1804-8	40275
	6	BS1806-8	40276		
<b>21"</b>	21" x 1-7/8" x .088" 525mm x 48mm x 2.25mm	.281" (7.00mm)	4	BS2104-8	40278
			6	BS2106-8	40279
<b>24"</b>	24" x 2-1/8" x .100" 600mm x 54mm x 2.50mm	.390" (10.00mm)	3	BS2403-0	40131
			4	BS2404-0	40282
<b>30"</b>	30" x 2-5/8" x .100" 750mm x 67mm x 2.50mm	.390" (10.00mm)	4	BS3004-0	40172



# POWER HACKSAW BLADES

## REDSTRIPE® SOLID HIGH SPEED STEEL – Power Hacksaw Blades

The solid, fully hardened molybdenum high speed steel composition of Redstripe® power hacksaw blades delivers extended life and efficient cutting action on a broad cross-section of materials. These blades can withstand heavier feed pressures and provide faster cut rates than blades made from composite designs. Redstripe® power hacksaw blades will effectively cut tough alloys such as stainless steels.

## REDSTRIPE® SOLID HIGH SPEED STEEL Power Hacksaw Blades



	Dimensions Length x Width x Thickness	Pinhole Diameter Inch (mm)	TPI (25mm)	Catalog No.	EDP No.
<b>12"</b>	12" x 1" x .050" 300mm x 25mm x 1.25mm	.281" (7.00mm)	10	RS1210-5	40046
			14	RS1214-5	40047
<b>14"</b>	14" x 1" x .050" 350mm x 25mm x 1.25mm	.281" (7.00mm)	10	RS1410-5	40049
			14	RS1414-5	40050
	14" x 1-1/4" x .062" 350mm x 32mm x 1.6mm	.281" (7.00mm)	6	RS1406-6	40051
			10	RS1410-6	40052
	14" x 1-1/2" x .075" 350mm x 38mm x 2mm	.281" (7.00mm)	6	RS1406-7	40054
<b>16"</b>	16" x 1-1/4" x .062" 400mm x 32mm x 1.5mm	.281" (7.00mm)	6	RS1606-5	40057
			10	RS1610-5	40058
<b>17"</b>	17" x 1" x .050" 425mm x 25mm x 1.25mm	.281" (7.00mm)	10	RS1710-5	40059
			14	RS1714-5	40060
	17" x 1-1/4" x .062" 425mm x 32mm x 1.5mm	.281" (7.00mm)	6	RS1706-6	40062
			10	RS1710-6	40063
<b>18"</b>	18" x 1-1/4" x .062" 450mm x 32mm x 1.6mm	.281" (7.00mm)	6	RS1806-6	40064
			10	RS1810-6	40065
	18" x 1-1/2" x .075" 450mm x 38mm x 2mm	.281" (7.00mm)	4	RS1804-7	40067
			6	RS1806-7	40068
			6	RS1806-8	40071
18" x 1-3/4" x .088" 450mm x 45mm x 2.25mm	.281" (7.00mm)	4	RS1804-8	40070	
<b>21"</b>	21" x 1-3/4" x .088" 525mm x 45mm x 2.25mm	.281" (7.00mm)	4	RS2104-8	40075
			6	RS2106-8	40076
<b>24"</b>	24" x 2" x .100" 600mm x 50mm x 2.50mm	.390" (10.00mm)	4	RS2404-0	40081
<b>30"</b>	30" x 2-1/2" x .100" 750mm x 63mm x 2.50mm	.390" (10.00mm)	4	RS3004-0	40083

## REDSTRIPE® SOLID HIGH SPEED STEEL Power Hacksaw Blades For KASTO and Other Metric Sized Machines



	Dimensions			Pinhole Diameter mm (Inch)	Teeth per 25mm (inch)	Catalog No.	EDP No.	Fits Kasto Machine Model No.
	Length	Width	Thickness					
<b>300mm</b>	300mm	32mm	2mm	8.5mm (.334")	6	RS300-6	16168	WBS 150-170
	12"	1-1/4"	.075"		10	RS300-10	16169	WBS 150-170
<b>350mm</b>	350mm	32mm	2mm	8.5mm (.334")	6	RS350-6	40177	UBS 200
	14"	1-1/4"	.075"		10	RS350-10	40178	UBS 200
<b>400mm</b>	400mm	32mm	2mm	8.5mm (.334")	4	RS400-4	40179	VBS242
	16"	1-1/4"	.075"		6	RS400-6	40180	VBS242
					10	RS400-10	40181	VBS242
<b>450mm</b>	450mm	38mm	2mm	8.5mm (.334")	4	RS450-4	40182	UBS 280
	18"	1-1/2"	.075"		6	RS450-6	40183	UBS 280
					10	RS450-10	40184	UBS 280
<b>500mm</b>	500mm	45mm	2mm	10.5mm (.413")	4	RS500-4	16170	BSM 323
	20"	1-3/4"	.075"		6	RS500-6	16171	BSM 323
					10	RS500-10	16172	BSM 323
<b>550mm</b>	550mm	45mm	2mm	10.5mm (.413")	4	RS550-4	40173	UBS 320
	22"	1-3/4"	.075"		6	RS550-6	40174	UBS 320
					10	RS550-10	40185	UBS 320
<b>575mm</b>	575mm	50mm	2.5mm	10.5mm (.413")	4	RS575-4	40175	EBS 320
	23"	2"	.100"		6	RS575-6	40176	EBS 320
<b>600mm</b>	600mm	50mm	2.5mm	10.5mm (.413")	4	RS600-4	16173	EBS 320AU
	24"	2"	.100"		6	RS600-6	16174	EBS 320AU
<b>650mm</b>	650mm	55mm	2.5mm	10.5mm (.413")	4	RS650-4	40186	EBS 400
	26"	2-3/16"	.100"		6	RS650-6	40187	EBS 400
<b>700mm</b>	700mm	55mm	2.5mm	10.5mm (.413")	4	RS700-4	40188	EBS 450
	28"	2-3/16"	.100"		6	RS700-6	40189	EBS 450
<b>850mm</b>	850mm	60mm	3mm	12.5mm (.492")	4	RS850-4	16175	EBS 550
	34"	2-3/8"	.118"		6	RS850-6	16176	EBS 550
<b>900mm</b>	900mm	114mm	3.5mm	12.5mm (.492")	2-1/2	RS900-2-1/2	68716	Marvel #24* †
<b>1000mm</b>	1000mm	126mm	3.5mm	12.5mm (.492")	2-1/2	RS1000-2-1/2	16177	PBS 630 †
	40"	5"	.138"					

\* Replacement For Marvel Cat. #3625-E  
† With 3 Pin Holes